



**IN THE CLAIMS**

(Currently Amended) A communication system comprising:

a mobile device including a Subscriber Identity Module (SIM) and an International Mobile Subscriber Identity (IMSI);

a first Mobile Subscriber Integrated Service Digital Network (MSISDN) number for use in a first public mobile network; a second MSISDN number for use in a second public mobile network; and

at least one signal gateway coupled among components of the first public mobile network and the second public mobile network, wherein the signal gateway couples calls between the SIM and the first public mobile network using the first MSISDN, wherein the signal gateway couples calls between the SIM and the second public mobile network using the second MSISDN, and wherein the signal gateway couples the calls without using an additional IMSI.

2. (Original) The system of claim 1, wherein at least one of the first MSISDN number and the second MSISDN number is permanently assigned to the SIM.

3. (Original) The system of claim 1, wherein at least one of the first MSISDN number and the second MSISDN number is temporarily assigned to the SIM.

4. (Original) The system of claim 1, wherein the first MSISDN number is a telephone number of the mobile device that is local to the first public mobile network.

5. (Original) The system of claim 1, wherein the second MSISDN number is a telephone number of the mobile device that is local to the second public mobile network.

6. (Original) The system of claim 1, wherein components of the signal gateway map the first MSISDN number to the second MSISDN number.

7. (Original) The system of claim 1, wherein at least one component of the signal gateway provides at least one of a home location register (HLR), a visited location register (VLR), a gateway mobile switching center (GMSC), a visited mobile switching center (VMSC), a short message service center (SMSC), and a service node in at least one of the first public mobile network and the second public mobile network.

8. (Original) The system of claim 1, wherein the signal gateway is coupled to at least one first mobile switching center of the first public mobile network and is coupled to provide signal loop-back at the first mobile switching center, wherein the signal gateway couples to at least one component of the second public mobile network via the first mobile switching center.

9. (Original) The system of claim 1, wherein the signal gateway is coupled to at least one second mobile switching center of the second public mobile network and is coupled to provide signal loop-back at the second mobile switching center, wherein the signal gateway couples to at least one component of the first public mobile network via the second mobile switching center.

10. (Original)        The system of claim 1, wherein the first public mobile network includes first and second mobile switching centers, wherein the at least one signal gateway includes first and second signal gateways coupled among the first and second mobile switching centers via couplings that support Signaling System Number 7 (SS7) protocols.

11. (Original)        The system of claim 10, wherein the first signal gateway couples to the first mobile switching center using a common signal point code, the first signal gateway couples to the second mobile switching center using a first signal point code, the second signal gateway couples to the first mobile switching center using a second signal point code, and the second signal gateway couples to the second mobile switching center using the common signal point code.

12. (Original)        The system of claim 10, wherein the first signal gateway couples to the first mobile switching center using a first signal point code and the second signal gateway couples to the second mobile switching center using a second signal point code.

13. (Original)        The system of claim 1, wherein the second public mobile network includes third and fourth mobile switching centers, wherein the at least one signal gateway includes third and fourth signal gateways coupled among the third and fourth mobile switching centers via couplings that support Signaling System Number 7 (SS7)

protocols.

14. (Original)        The system of claim 13, wherein the third signal gateway couples to the third mobile switching center using a common signal point code, the third signal gateway couples to the fourth mobile switching center using a first signal point code, the fourth signal gateway couples to the third mobile switching center using a second signal point code, and the fourth signal gateway couples to the fourth mobile switching center using the common signal point code.

15. (Original)        The system of claim 13, wherein the third signal gateway couples to the third mobile switching center using a first signal point code and the fourth signal gateway couples to the fourth mobile switching center using a second signal point code.

16. (Original)        The system of claim 1, wherein the mobile device includes at least one of cellular telephones, personal computers, portable computing devices, portable telephones, portable communication devices, subscriber devices or units, and personal digital assistants.

17. (Currently Amended)    A communication system comprising:

means for wireless communications;

means for associating a single subscriber identity with the means for wireless communications; and

means for coupling calls among the means for wireless communications and a first public mobile network using a first telephone number and for coupling calls among the means for wireless communications and a second public network using a second telephone number, wherein the means include a signal gateway at a Home Public Mobile Network (HPMN) without using a Roaming Service Provider Node (RSPN) at a partner Visitor Public Mobile Network (VPMN).

18. (Currently Amended) A system comprising a wireless client device that includes:

one Subscriber Identity Module (SIM) having one assigned International Mobile Subscriber Identity (IMSI), and

at least one signal gateway that supports use of two or more Mobile Subscriber Integrated Service Digital Network (MSISDN) numbers by the client device,

wherein the signal gateway couples among at least one of first and second mobile switching centers,

wherein the signal gateway couples calls between the client device and the first mobile switching center using a first MSISDN and couples calls between the client device and a second mobile switching center using a second MSISDN, wherein the calls are coupled without using an additional IMSI.

19. (Currently Amended) A device comprising:

at least one signal gateway coupled among components of a first public mobile network and a second public mobile network,

wherein the signal gateway couples calls between a mobile device and the first public mobile network using a first Mobile Subscriber Integrated Service Digital Network (MSISDN) number,

wherein the signal gateway couples calls between the SIM and the second public mobile network using a second MSISDN,

wherein the mobile device includes a single Subscriber Identity Module (SIM) and a single International Mobile Subscriber Identity (IMSI).

20. (Original) The device of claim 19, wherein the first MSISDN number is a telephone number of the mobile device that is local to the first public mobile network and the second MSISDN number is a telephone number of the mobile device that is local to the second public mobile network.

21. (Original) The device of claim 19, wherein the signal gateway maps the first MSISDN number to the second MSISDN number.

22. (Original) The device of claim 19, wherein the signal gateway provides at least one of a home location register (HLR), a visited location register (VLR), a gateway mobile switching center (GMSC), a visited mobile switching center (VMSC), a short message service center (SMSC), and a service node in at least one of the first and second public mobile networks.

23. (Original) The device of claim 19, wherein the signal gateway is coupled to at

least one first mobile switching center of the first public mobile network and is coupled to provide signal loop-back at the first mobile switching center, wherein the signal gateway couples to at least one component of the second public mobile network via the first mobile switching center.

24. (Original)        The device of claim 19, wherein the signal gateway is coupled to at least one second mobile switching center of the second public mobile network and is coupled to provide signal loop-back at the second mobile switching center, wherein the signal gateway couples to at least one component of the first public mobile network via the second mobile switching center.

25. (Original)        The device of claim 19, wherein the first public mobile network includes first and second mobile switching centers, wherein the at least one signal gateway includes first and second signal gateways coupled among the first and second mobile switching centers via couplings that support Signaling System Number 7 (SS7) protocols.

26. (Original)        The device of claim 25, further comprising cross-connections between the first and second signal gateways and the first and second mobile switching centers.

27. (Original)        The device of claim 19, wherein the second public mobile network includes third and fourth mobile switching centers, wherein the at least one signal

gateway includes third and fourth signal gateways coupled among the third and fourth mobile switching centers via couplings that support Signaling System Number 7 (SS7) protocols.

28. (Original)        The device of claim 27, further comprising cross-connections between the third and fourth signal gateways and the third and fourth mobile switching centers.

29. (Original)        The device of claim 19, wherein the mobile device includes at least one of cellular telephones, personal computers, portable computing devices, portable telephones, portable communication devices, subscriber devices or units, and personal digital assistants.

30. (Currently Amended)    A method for supporting multiple Mobile Subscriber Integrated Service Digital Network (MSISDN) numbers in a mobile device, comprising:

- connecting calls between the mobile device and a first public mobile network using a first MSISDN that is associated with the first public mobile network, wherein the mobile device includes a Subscriber Identity Module (SIM) with an International Mobile Subscriber Identity (IMSI);
- mapping the first MSISDN number to a second MSISDN number that is associated with a second public mobile network; and
- connecting calls between the client device and the second public mobile network using the second MSISDN via a coupling through the first public mobile network without



using an additional IMSI.

31. (Original)        The method of claim 30, wherein the IMSI is associated with the first public mobile network.

32. (Original)        The method of claim 30, wherein connecting calls between the mobile device and the first public mobile network comprises coupling calls between the first public mobile network and the SIM via at least one signal gateway, wherein the signal gateway is coupled among components of the first public mobile network and the second public mobile network.

33. (Original)        The method of claim 30, wherein the first MSISDN number is a telephone number of the mobile device that is local to the first public mobile network and the second MSISDN number is a telephone number of the mobile device that is local to the second public mobile network.

34. (Original)        The method of claim 30, wherein components of a signal gateway coupled to at least one of the first and second public mobile networks map the first MSISDN number to the second MSISDN number.

35. (Original)        The method of claim 30, wherein connecting calls between the mobile device and each of the first and second public mobile networks includes coupling the first and second public networks using at least one signal gateway, wherein at least

one component of the signal gateway provides at least one of a home location register (HLR), a visited location register (VLR), a gateway mobile switching center (GMSC), a visited mobile switching center (VMSC), a short message service center (SMSC), and a service node in at least one of the first public mobile network and the second public mobile network.

36. (Original)           The method of claim 30, wherein connecting calls between the mobile device and each of the first and second public mobile networks includes coupling at least one signal gateway to at least one first mobile switching center of the first public mobile network to provide signal loop-back at the first mobile switching center, wherein the signal gateway couples to at least one component of the second public mobile network via the first mobile switching center.

37. (Original)           The method of claim 30, wherein connecting calls between the mobile device and each of the first and second public mobile networks includes coupling at least one signal gateway to at least one second mobile switching center of the second public mobile network to provide signal loop-back at the second mobile switching center, wherein the signal gateway couples to at least one component of the first public mobile network via the second mobile switching center.

38. (Original)           The method of claim 30, wherein the mobile device includes at least one of cellular telephones, personal computers, portable computing devices, portable telephones, portable communication devices, subscriber devices or units, and

personal digital assistants.

39. (Currently Amended) A computer readable medium including executable instructions which, when executed, provide numerous Mobile Subscriber Integrated Service Digital Network (MSISDN) numbers in a mobile device, by:

connecting calls between the mobile device and a first public mobile network using a first MSISDN that is associated with the first public mobile network, wherein the mobile device includes a Subscriber Identity Module (SIM) with an International Mobile Subscriber Identity (IMSI);

mapping the first MSISDN number to a second MSISDN number that is associated with a second public mobile network; and

connecting calls between the client device and the second public mobile network using the second MSISDN via a coupling through the first public mobile network without using an additional IMSI.

40. (New) A communication system comprising:

a mobile device including a Subscriber Identity Module (SIM) and an International Mobile Subscriber Identity (IMSI);

a first Mobile Subscriber Integrated Service Digital Network (MSISDN) number for use in a first public mobile network;

a plurality of second MSISDN numbers for use in at least one second public mobile network; and

at least one signal gateway coupled among components of the first public mobile network and the second public mobile network, wherein the signal gateway couples calls between the SIM and the first public mobile network using the first MSISDN, wherein the signal gateway automatically couples calls between the SIM and the second public mobile network using one of the plurality of second MSISDNs without using an additional IMSI.

41. (New) The system of claim 40, wherein at least one of the first MSISDN number and one of the plurality of second MSISDN numbers is permanently assigned to the SIM.

42. (New) The system of claim 40, wherein at least one of the first MSISDN number and the plurality of second MSISDN numbers is temporarily assigned to the SIM.

43. (New) The system of claim 40, wherein the first MSISDN number is a telephone number of the mobile device that is local to the first public mobile network.

44. (New) The system of claim 40, wherein the plurality of second MSISDN numbers are telephone numbers of the mobile device that are local to the second public mobile network.

45. (New) The system of claim 40, wherein components of the signal gateway map the first MSISDN number to one of the plurality of second MSISDN numbers.

46. (New) The system of claim 40, wherein at least one component of the signal gateway provides at least one of a home location register (HLR), a visited location register (VLR), a gateway mobile switching center (GMSC), a visited mobile switching center (VMSC), a short message service center (SMSC), and a service node in at least one of the first public mobile network and the second public mobile network.

47. (New) The system of claim 40, wherein the signal gateway is coupled to at least one first mobile switching center of the first public mobile network and is coupled to provide signal loop-back at the first mobile switching center, wherein the signal gateway couples to at least one component of the second public mobile network via the first mobile switching center.

48. (New) The system of claim 40, wherein the signal gateway is coupled to at least one second mobile switching center of the second public mobile network and is coupled to provide signal loop-back at the second mobile switching center, wherein the signal gateway couples to at least one component of the first public mobile network via the second mobile switching center.

49. (New) A method for supporting multiple Mobile Subscriber Integrated Service Digital Network (MSISDN) numbers in a mobile device, comprising:

connecting calls between the mobile device and a first public mobile network using a first MSISDN number that is associated with the first public mobile network, wherein the mobile device includes a Subscriber Identity Module (SIM) with an International Mobile Subscriber Identity (IMSI);

mapping the first MSISDN number to one of a plurality of second MSISDN numbers that are associated with a second public mobile network; and

automatically connecting calls between the client device and the second public mobile network using one of the plurality of second MSISDN numbers via a coupling through the first public mobile network without using an additional IMSI.

50. (New) The method of claim 49, wherein the IMSI is associated with the first public mobile network.

51. (New) The method of claim 49, wherein connecting calls between the mobile device and the first public mobile network comprises coupling calls between the first public mobile network and the SIM via at least one signal gateway, wherein the signal gateway is coupled among components of the first public mobile network and the second public mobile network.

52. (New) The method of claim 49, wherein the first MSISDN number is a telephone number of the mobile device that is local to the first public mobile network and the plurality of second MSISDN numbers are telephone numbers of the mobile device that are local to the second public mobile network.

53. (New) The method of claim 51, wherein the IMSI is associated with the first MSISDN number at the first public mobile network, and wherein the plurality of second MSISDN numbers are in a designated range of numbers defined by the second public mobile network.

54. (New) The method of claim 53, wherein the signal gateway serves as a home location register (HLR) for the designated range of numbers.

55. (New) The method of claim 49, wherein the plurality of second MSISDN numbers each have a different profile in the second public network.

56. (New) The method of claim 49, wherein components of a signal gateway coupled to at least one of the first and second public mobile networks map the first MSISDN number to one of the plurality of second MSISDN numbers.

57. (New) The method of claim 49, wherein connecting calls between the mobile device and each of the first and second public mobile networks includes coupling the first and second public networks using at least one signal gateway, wherein at least one component of the signal gateway provides at least one of a home location register (HLR), a visited location register (VLR), a gateway mobile switching center (GMSC), a visited mobile switching center (VMSC), a short message service center (SMSC), and a

service node in at least one of the first public mobile network and the second public mobile network.

58. (New) The method of claim 49, wherein connecting calls between the mobile device and each of the first and second public mobile networks includes coupling at least one signal gateway to at least one first mobile switching center of the first public mobile network to provide signal loop-back at the first mobile switching center, wherein the signal gateway couples to at least one component of the second public mobile network via the first mobile switching center.

59. (New) The method of claim 49, wherein connecting calls between the mobile device and each of the first and second public mobile networks includes coupling at least one signal gateway to at least one second mobile switching center of the second public mobile network to provide signal loop-back at the second mobile switching center, wherein the signal gateway couples to at least one component of the first public mobile network via the second mobile switching center.

60. (New) The method of claim 49, wherein the mobile device includes at least one of cellular telephones, personal computers, portable computing devices, portable telephones, portable communication devices, subscriber devices or units, and personal digital assistants.



61. (New) A method for supporting Mobile Subscriber Integrated Service Digital Network (MSISDN) numbers in an inbound roaming mobile device, comprising:

- registering the mobile device in a public mobile network in which the mobile device is roaming;
- the public mobile network accepting the registration of the mobile device;
- the public mobile network sending messages to a signal gateway; and
- the signal gateway determining whether the mobile device is a subscriber to a temporary local number service.

62. (New) The method of claim 61, further comprising:

- if the mobile device is a subscriber;
- modifying a calling Global Title (GT) to a signal gateway GT; and
- relaying a registration message to the public mobile network with the modified GT.

63. (New) The method of claim 62, further comprising the public mobile network mapping a local MSISDN for use of the roaming mobile device.

64. (New) A method for supporting Mobile Subscriber Integrated Service Digital Network (MSISDN) numbers in inbound roaming mobile device, comprising:

- registering the mobile device in a foreign public mobile network, wherein signaling related to the registering is directed through a signaling gateway coupling a

home network of the mobile device and the foreign public mobile network without using a Roaming Service Provider Node (RSPN) at the foreign public mobile network; and transmitting a welcome message to the mobile device, wherein the message comprises and offer to receive incoming calls from within the foreign public mobile network at preferred rates while registered with the foreign public mobile network.

65. (New) The method of claim 64, further comprising the foreign public mobile network assigning a temporary local number to the mobile device.

66. (New) The method of claim 64, further comprising;  
assigning a temporary local number to the mobile device; and  
transmitting the temporary local number to the mobile device via a Short Message Service (SMS) message.

67. (New) The method of claim 65, further comprising the signal gateway issuing an InsertSubscriberData to a Visited Location Register (VLR) location of the mobile device in the foreign public mobile network.